# SAFETY DATA SHEET

#### 1. Identification

**Product identifier** X-TREME WHITE

Other means of identification

08670 109206 713 **Product Code** Recommended use Not available.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Quest Industrial Products, LLC. Company name N92 W14701 Anthony Avenue **Address** Menomonee Falls, WI 53051

**United States** 

Phone Telephone (262) 255-9500

Website quest-ip.com E-mail info@guest-ip.com

**Emergency phone number** Chemtrec Phone 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

> Liquefied gas Gases under pressure

**Health hazards** Category 4 Acute toxicity, oral

> Category 2A Serious eye damage/eye irritation

Carcinogenicity Category 2

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if

swallowed. Causes serious eye irritation. Suspected of causing cancer.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this

product. Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water Response

> for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Rinse mouth. If eye irritation persists: Get

medical advice/attention.

Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do **Storage** 

not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 44.18% of the mixture consists of component(s) of unknown acute oral toxicity.

Material name: X-TREME WHITE SDS US

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ETHYL ACETATE		141-78-6	10 to <20
PROPANE		74-98-6	10 to <20
CALCIUM CARBONATE		1317-65-3	5 to <10
TITANIUM DIOXIDE		13463-67-7	5 to <10
MINERAL SPIRITS		64741-65-7	1 to <5
N-BUTANE		106-97-8	1 to <5
PETROLEUM NAPHTHA		8032-32-4	1 to <5
Other components below reportable	levels		50 to <60

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Call a physician if symptoms develop or persist.

Skin contact No adverse effects due to skin contact are expected. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

No specific first aid measures noted.

Not likely, due to the form of the product. Rinse mouth. If vomiting occurs, keep head low so that Ingestion

stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

**General information** 

media

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when

exposed to heat or flame.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Secure cylinders in an upright position at all times, close all valves when not in use. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

#### Occupational exposure limits

Components	Туре	Value	Form
CALCIUM CARBONATE (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction
,		15 mg/m3	Total dust.
ETHYL ACETATE (CAS 141-78-6)	PEL	1400 mg/m3	
		400 ppm	
MINERAL SPIRITS (CAS 64741-65-7)	PEL	400 mg/m3	
		100 ppm	
PROPANE (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values	•		
Components	Туре	Value	
ETHYL ACETATE (CAS 141-78-6)	TWA	400 ppm	
N-BUTANE (CAS 106-97-8)	STEL	1000 ppm	
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
CALCIUM CARBONATE (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total
ETHYL ACETATE (CAS 141-78-6)	TWA	1400 mg/m3	
•		400 ppm	

Material name: X-TREME WHITE

SDS US

US. NIOSH: Pocket Guide to Chem Components	nical Hazards Type	Value	Form
MINERAL SPIRITS (CAS 64741-65-7)	TWA	400 mg/m3	
,		100 ppm	
N-BUTANE (CAS 106-97-8)	TWA	1900 mg/m3	
,		800 ppm	
PETROLEUM NAPHTHA (CAS 8032-32-4)	Ceiling	1800 mg/m3	
,	TWA	350 mg/m3	
PROPANE (CAS 74-98-6)	TWA	1800 mg/m3	
,		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** For prolonged or repeated skin contact use suitable protective gloves.

Other Wear suitable protective clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or

smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

Form Aerosol. Liquefied gas.

Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -305.68 °F (-187.6 °C) estimated Initial boiling point and boiling -43.78 °F (-42.1 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit lawer 2.4.9/

Flammability limit - lower

2.4 % estimated

(%)

Flammability limit - upper

9.5 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 1862.85 hPa estimated

Vapor densityNot available.Relative densityNot available.

Material name: X-TREME WHITE

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 800 °F (426.67 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 7.69 lbs/gal

Flammability class Flammable IA estimated

Heat of combustion (NFPA 10.58 kJ/g estimated

30B)

Percent volatile 79.86 Specific gravity 0.92

VOC 4.8612296 lbs/gal Regulatory

582.503774 g/l Regulatory 3.061117 lbs/gal Material 366.802713 g/l Material

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsHazardous decompositionAcids. Strong oxidizing agents. Nitrates. Fluorine.No hazardous decomposition products are known.

products

### 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

**Ingestion** Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

**Test Results** Components **Species** ETHYL ACETATE (CAS 141-78-6) Acute Inhalation LC50 Rat 16000 ppm, 6 Hours LD50 Mouse 1500 ppm, 4 Hours Rabbit 2500 ppm, 4 Hours Rat 4000 ppm, 4 Hours Oral LD50 Mouse 0.44 g/kg Rabbit 4.9 g/kg Rat 11.3 ml/kg

Material name: X-TREME WHITE

sps us 5 / 10

08670 109206 713 Version #: 02 Revision date: 05-06-2015 Issue date: 04-20-2015

**Species Test Results** Components

MINERAL SPIRITS (CAS 64741-65-7)

**Acute** Inhalation

LC50 Rat 61 mg/l, 4 Hours

Oral

LD50 Rat > 25 ml/kg

N-BUTANE (CAS 106-97-8)

**Acute** Inhalation

LC50 Mouse 680 mg/l, 2 Hours

> Rat 658 mg/l, 4 Hours

5.6 g/kg

PETROLEUM NAPHTHA (CAS 8032-32-4)

Acute

Inhalation

LC50 Rat 3400 mg/l, 4 Hours

PROPANE (CAS 74-98-6)

**Acute** Inhalation

LC50 Rat > 1442.847 mg/l, 15 Minutes

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Suspected of causing cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Test Results** Components **Species** 

ETHYL ACETATE (CAS 141-78-6)

Aquatic

Fish LC50 Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours

Material name: X-TREME WHITE SDS US 6 / 10

**Species Test Results** Components MINERAL SPIRITS (CAS 64741-65-7) **Aquatic** 2.7 - 5.1 mg/l, 48 hours EC50 Water flea (Daphnia pulex) Crustacea Fish LC50 Rainbow trout, donaldson trout 8.8 mg/l, 96 hours (Oncorhynchus mykiss) 8.8 mg/l, 96 hours TITANIUM DIOXIDE (CAS 13463-67-7) **Aquatic** 

Water flea (Daphnia magna)

Mummichog (Fundulus heteroclitus)

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Crustacea

Fish

Partition coefficient n-octanol / water (log Kow)

ETHYL ACETATE 0.73 **N-BUTANE** 2.89 **PROPANE** 2.36

EC50

LC50

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions** 

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

> 1000 mg/l, 48 hours

> 1000 mg/l, 96 hours

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

### 14. Transport information

DOT

UN1950 **UN** number

**UN** proper shipping name

Transport hazard class(es)

Aerosols, flammable, 2.1

Class Not available.

Subsidiary risk

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

**UN number** UN1950

Aerosols, flammable, 2.1 UN proper shipping name

Transport hazard class(es)

Class Not available.

Subsidiary risk

Packing group Not applicable.

No. **Environmental hazards** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Forbidden. Passenger and cargo

aircraft

Material name: X-TREME WHITE 08670 109206 713 Version #: 02 Revision date: 05-06-2015 Issue date: 04-20-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Forbidden. Cargo aircraft only

**IMDG** 

**UN** number UN1950

**UN** proper shipping name Aerosols, flammable, 2.1

Transport hazard class(es)

Not available. Class

Subsidiary risk

Not applicable. **Packing group** 

**Environmental hazards** 

Marine pollutant No.

**EmS** Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

# 15. Regulatory information

**US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

ETHYL ACETATE (CAS 141-78-6) Listed. N-BUTANE (CAS 106-97-8) Listed. PROPANE (CAS 74-98-6) Listed.

Not established.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** 

> Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Nο

chemical

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-BUTANE (CAS 106-97-8) PROPANE (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

#### **US** state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

MINERAL SPIRITS (CAS 64741-65-7)

Material name: X-TREME WHITE SDS US 8 / 10 N-BUTANE (CAS 106-97-8)

PETROLEUM NAPHTHA (CAS 8032-32-4)

TITANIUM DIOXIDE (CAS 13463-67-7)

#### **US. Massachusetts RTK - Substance List**

CALCIUM CARBONATE (CAS 1317-65-3)

ETHYL ACETATE (CAS 141-78-6)

MINERAL SPIRITS (CAS 64741-65-7)

N-BUTANE (CAS 106-97-8) PROPANE (CAS 74-98-6)

TITANIUM DIOXIDE (CAS 13463-67-7)

#### US. New Jersey Worker and Community Right-to-Know Act

CALCIUM CARBONATE (CAS 1317-65-3)

ETHYL ACETATE (CAS 141-78-6)

N-BUTANE (CAS 106-97-8)

PETROLEUM NAPHTHA (CAS 8032-32-4)

PROPANE (CAS 74-98-6)

TITANIUM DIOXIDE (CAS 13463-67-7)

#### US. Pennsylvania Worker and Community Right-to-Know Law

CALCIUM CARBONATE (CAS 1317-65-3)

ETHYL ACETATE (CAS 141-78-6)

MINERAL SPIRITS (CAS 64741-65-7)

N-BUTANE (CAS 106-97-8)

PETROLEUM NAPHTHA (CAS 8032-32-4)

PROPANE (CAS 74-98-6)

TITANIUM DIOXIDE (CAS 13463-67-7)

#### **US. Rhode Island RTK**

ETHYL ACETATE (CAS 141-78-6) N-BUTANE (CAS 106-97-8) PROPANE (CAS 74-98-6)

#### **US.** California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004 SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7) Listed: October 1, 1988 TITANIUM DIOXIDE (CAS 13463-67-7) Listed: September 2, 2011

#### **International Inventories**

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information, including date of preparation or last revision

 Issue date
 04-20-2015

 Revision date
 05-06-2015

Version # 02

Material name: X-TREME WHITE SDS US

On inventory (yes/no)\*

HMIS® ratings Health: 2\*

Flammability: 4 Physical hazard: 0

NFPA ratings

Health: 2 Flammability: 4 Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Material name: X-TREME WHITE